

Product Information Specialty Lubricants



DOW CORNING

Molykote[®] G-N PLUS Solid Lubricant Paste

FEATURES & BENEFITS

- High load-carrying capacity
- Low coefficient of friction
- Prevents frictional corrosion and scoring
- Protection from stick-slip
- Good anti-corrosion properties
- Reduces formation of fretting corrosion
- Simplifies dismantling processes
- High surface covering capacity (40 m²/kg)

COMPOSITION

- Mineral oil
- Solid lubricants
- Thickener

Supplied by:
Sil-Mid Limited
Roman Park, Roman Way
Coleshill, West Midlands
B46 1HG. UK
T: 01675 432850
E: info@silmid.com

Emergency Telephone No. +44 (0)1675 432850
(Monday to Friday, 08:00 – 17:30 – GMT)

Solid lubricant paste for the assembly and running-in of metal components

APPLICATIONS

- Press-fit production of all types of machine elements, as a running-in lubricant for new machines and gear-boxes
- Permanent lubrication of machine elements that are moved only rarely or slightly and also for drilling, sawing and thread cutting
- Used successfully for lubricating threaded spindles, splined shafts, toothed gears, worm and transmission gears, screws, valves, pumps, machine-tool guides and also for the tightening and fitting of roller bearings, washers, wheels, flanges and bolts

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales office or your Global Dow Corning Connection before writing specifications on this product.

Test ¹	Property	Unit	Result
	Color		Black
Penetration, Density			
ISO 2137	Unworked penetration	mm/10	280–310
ISO 2811	Density at 20°C (68°F)	g/ml	1.35
Temperature			
	Service temperature ²	°C	-25 to +450 with reduced air access +630
		°F	-13 to +842 with reduced air access +1166
Load-carrying Capacity, Wear Protection, Service Life			
	Four-ball tester		
DIN 51 350 pt.4	Weld load	N	2800
DIN 51 350 pt.5	Wear scar under 800 N load	mm	0.75
	Almen-Wieland machine		
	OK load	N	> 20000
	Frictional force	N	2600

¹ISO: International Standardization Organization

DIN: Deutsche Industrie Norm

²Temperature resistance of solid lubricants

HOW TO USE

How to Apply

Clean the sliding surfaces or contact areas, then apply paste with a brush, cloth, synthetic sponge or window leather. Do not use in excess as with grease lubrication. Vigorous rubbing into metal surface will improve adhesion. Do not mix with greases or oils.

HANDLING

PRECAUTIONS

PRODUCT SAFETY

INFORMATION REQUIRED

FOR SAFE USE IS NOT

INCLUDED IN THIS

DOCUMENT. BEFORE

HANDLING, READ PRODUCT

AND SAFETY DATA SHEETS

AND CONTAINER LABELS FOR

SAFE USE, PHYSICAL AND

HEALTH HAZARD

INFORMATION. THE SAFETY

DATA SHEET IS AVAILABLE ON

THE DOW CORNING WEBSITE

AT DOWCORNING.COM, OR

FROM YOUR DOW CORNING

SALES APPLICATION

ENGINEER, OR DISTRIBUTOR,

OR BY CALLING

DOW CORNING CUSTOMER

SERVICE.

USABLE LIFE AND

STORAGE

When stored between 0°C and 40°C in the original unopened containers, this product has a usable life of 60 months from the date of production.

PACKAGING

INFORMATION

Molykote[®] G-N PLUS Solid Lubricant Paste is available in different standard container sizes. Detailed container size information should be obtained from your nearest Dow Corning sales office or Dow Corning distributor.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

TYPICAL PROPERTIES (continued)

Test	Property	Unit	Result
Coefficient of Friction			
	Press-Fit test	μ	0.08, no scatter
	Screw test: Erichsen ³		
	Screw test - μ thread		0.12
	Screw test - μ head		0.06
Resistance			
DIN 51 807 pt.1	Water resistance, static, evaluation		2-90

³Coefficient of friction in bolted connection, M12, 8.8, on blackened surface

HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Product Safety and Regulatory Compliance (PS&RC) specialists available in each area.

For further information, please see our website, dowcorning.com or consult your local Dow Corning representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

We help you invent the future.[™]

molykote.com